

Ultrasonic Cleaning Systems for Medical and Industry

Product name	Code	
SONICA 5300 M S3 *	090.003.0034	
SONICA 5300 MH S3 *	090.003.0035	
SONICA 5300 ETH S3 *	090.003.0036	
SONICA 5300 EP S3 *	090.003.0037	
Ultrasonic Cleaner 28 Litres		
Accessories		
Stainless steel wire basket Internal dim. 460x260x90mm	090.004.0010	
Stainless steel lid 5200/5300	090.004.0025	
Stainless steel auxiliary tank SONICA 5300 Indicative dim. 500x300x200mm	090.004.0048	
Stainless steel beaker holder for two glass or plastic beaker	090.004.0036	
Plastic beaker 250 ml	090.004.0032	
Glass beaker 400 ml	090.004.0033	
Further accessories on request		

SONICA[®] 5300 S3



* Stainless steel tank made in AISI 304 thickness 08/10 with round tank corners for a better removing of dirt residuals after cleaning process. The tank is conical and realized with a press machine

General Characteristics

Ultrasonic Cleaning is a safe and efficient modern procedure, which ensures perfect cleaning within the shortest time possible. It has many advantages over ordinary cleaning methods. Ultrasonics can remove even the most tenacious deposits from parts which would be difficult to reach by hand, it also reduces the risk of injury or infection which may occur during manual cleaning.

Notes for use as "Medical Devices"

Denomination: Ultrasonic Cleaning Device UMDNS-nomenclature (ECRI) 14-263 **Field of application**: Cleaning and disinfection of surgical and dental instruments **Classification** (Medical Devices Directive 93/42/EEC, appendix IX): Class I, Non Active MD, Non Invasive MD, Non Implantable MD

"Medical Device" registration and classification

Registration Number: 103291/R SOLTEC Srl CND Classification: Z12011302 Ultrasonic Cleaning Device

SOLTEC S.r.l.

Uffici Commerciali e Sede Legale: Via G. Röntgen 16 - 20136 Milano Tel. +39 02 58 308 378 - Fax +39 02 58 308 595 - www.soltec.it - info@soltec.it Produzione e Magazzino: Via G. Castelbarco, 17 - 20136 Milano - Tel. +39 02 58 324 131

Cod. fisc. e P.IVA: IT11127210158 N. Mecc.: MI 221750 - C.C.I.A.A. Milano N. 1441548 Iscr. Trib. Mi Reg. Soc. N. 343391/8444/41 Cap. Soc. Euro 110.500 i.v. - Iscr. Registro AEE Nr. IT0802000000435



SONICA® Lavatrici ad Ultrasuoni - SONICA® Ultrasonic Cleaners - SONICA® Ultraschall - Reinigungsgeräte



Technical Data

Rev.2-04-2020

SONICA

Technical specification subject to change

Main line voltage	230/240V~50/60Hz	
Main input power/consumption	500 W	
Main input power with heating	1500 W	
Peak HF Ultrasound Power	1000 W	
US frequency	39 kHz ± 1 kHz with SWEEP SYSTEM Technology	
Liquid drain	1/2"	
Transducers	10 (2 Piezoelectric ceramics each)	
Tank capacity [L]	28	
Weight [KG]	15	
Installation category	Class II according to EN 61010-1	
Environmental conditions	Temperature Rel. Hum. 80% up to 31°C with linear	
	decrease up to 50% at 40°C	
IP grade	IP 22	
CE-compliant	2004/108/EC EMC Directive (EN61326)	
	2006/95/EC LV Directive (EN 61010-1)	
	93/42/CEE Medical Device Directive	
	Risk Class I according to the rule 12 to the Directive 93/42/EEC Annex IX	


Approximately Internal Tank Dimensions

External Appliance Dimensions

W/D/H (mm)	500 / 300 / 200	W/D/H (mm)	600 / 330 / 425
Max filling volume tank	28 L	Max operating tank volume	25 L

Constructive Materials

Housing	Stainless steel AISI 304
Tank	Stainless steel AISI 304



Control panel available series



timer which can be set for 15 minutes. It can also be set to manual operation.up to 1 hour of continuous. No heating system Sweep System generator

minutes. It can also be set to manual operation.up to 1 hour of continuous. The thermostat for the heater is set at 60°C.

Sweep System generator

by a microprocessor. minutes. Double washing times 10-20-30 minutes by pressing twice the minutes key Sweep System generator

M serie: The simplest version in the MH serie: This version is equipped ETH serie: Cleaning times and EP serie: The most technologically SONICA range is equipped with a with a timer which can be set for 15 temperature controlled electronically advanced of the SONICA range: Sweep System generator; modern Ultrasonic cleaning times 5-10-15 digital display control panel window; degas time setting; cleaning times from 0 to 99 minutes; tank liquid temperature setting up to 70°C; memory for 9 cleaning programmes; jet program function to start quickly and easily cleaning cycle.

SOLTEC Srl - Via G.Rontgen 16 - 20136 Milano - Italy- Tel +39 0258308378 - Fax +39 0258308595 info@soltec.it https://www.soltec.it Facebook https://www.facebook.com/soltec.ultrasonics LinkedIn https://www.linkedin.com/company/soltec-srl