

Ultrasonic Cleaning Systems for Medical and Industry

Product name	Code
SONICA ATC 67L EP S3*	090.003.0041
Ultrasonic Cleaner	
Stainless steel wire basket Internal dim. 560x280x240mm	090.004.0015
Stainless steel lid	090.004.0031
Stainless steel auxiliary tank SONICA 5300 Indicative dim. 500x300x200mm	090.004.0048

Further accessories on request

SONICA[®] 67 Litres



* Special stainless steel tank made in AISI 316Ti thickness 20/10 with round tank corners for a better removing of dirt residuals after cleaning process. The tank is welded with TIG process

General Characteristics

Ultrasonic Cleaning is a safe and efficient modern procedure, which ensures perfect cleaning within the shortest time possible. It has many advantages over ordinary cleaning methods. Ultrasonics can remove even the most tenacious deposits from parts which would be difficult to reach by hand, it also reduces the risk of injury or infection which may occur during manual cleaning.

Notes for use as "Medical Devices"

Denomination: Ultrasonic Cleaning Device UMDNS-nomenclature (ECRI) 14-263 **Field of application**: Cleaning and disinfection of surgical and dental instruments **Classification** (Medical Devices Directive 93/42/EEC, appendix IX): Class I, Non Active MD, Non Invasive MD, Non Implantable MD

"Medical Device" registration and classification

Registration Number: 103291/R SOLTEC Srl CND Classification: Z12011302 Ultrasonic Cleaning Device

SOLTEC S.r.l.

Uffici Commerciali e Sede Legale: Via G. Röntgen 16 - 20136 Milano Tel. +39 02 58 308 378 - Fax +39 02 58 308 595 - www.soltec.it - info@soltec.it Produzione e Magazzino: Via G. Castelbarco, 17 - 20136 Milano - Tel. +39 02 58 324 131

Cod. fisc. e P.IVA: IT11127210158 N. Mecc.: MI 221750 - C.C.I.A.A. Milano N. 1441548 Iscr. Trib. Mi Reg. Soc. N. 343391/8444/41 Cap. Soc. Euro 110.500 i.v. - Iscr. Registro AEE Nr. IT0802000000435



SONICA® Lavatrici ad Ultrasuoni - SONICA® Ultrasonic Cleaners - SONICA® Ultraschall - Reinigungsgeräte



Technical Data

SONICA® 67 Litres

Technical specification subject to change

Main line voltage	230/240V~50/60Hz		
Main input power/consumption	600 W		
Main input power with heating	2100 W		
Peak HF Ultrasound Power	1200 W		
US frequency	39 kHz ± 1 kHz with SWEEP SYSTEM Technology		
Liquid drain	1/2"		
Transducers	14 (2 Piezoelectric ceramics each)		
Tank capacity [L]	67		
Weight [KG]	30		
Installation category	Class II according to EN 61010-1		
Environmental conditions	Temperature Rel. Hum. 80% up to 31°C with linear		
	decrease up to 50% at 40°C		
IP grade	IP 22		
CE-compliant	2004/108/EC EMC Directive (EN61326)		
	2006/95/EC LV Directive (EN 61010-1)		
	93/42/CEE Medical Device Directive		
	Risk Class I according to the rule 12 to the Directive 93/42/EEC Annex IX		


Effective Tank Internal Dimensions

External Appliance Dimensions

W/D/H (mm)	600 / 320 / 350	W/D/H (mm)	660 / 380 / 570
Max filling volume tank	67 L	Max operating tank volume	61 L

Constructive Materials

Housing	Stainless steel AISI 304
Tank	Stainless steel AISI 316Ti 20/10



Control panel available series

М	МН	ETH	EP
NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE	SONICA UIRADOLC CLARER DIRADOLC DIRADOLC DIRADOL

EP serie: The most technologically advanced of the SONICA range: **Sweep System** generator; modern digital display control panel window; degas time setting; cleaning times from 0 to 99 minutes; tank liquid temperature setting up to 70°C; memory for 9 cleaning programmes; jet program function to start quickly and easily cleaning cycle.